PMB Moisture Analyser





With outstanding connectivity and rapid test time, PMB moisture analysers offer the top value in their class. An automatic test-setting function enables easy recall for frequent testing of the same material without additional user programming. USB and RS-232 interfaces let you connect the PMB to a computer or printer. Store results and test programs for future reference with a USB memory stick or PMB's builtin memories. Three heating options offer the flexibility to customise test methods and temperatures. PMB helps free up time for busy lab professionals by allowing them to quickly perform moisture analysis and share test results easily with colleagues.

Superior connectivity in a moisture analyser, with two USB ports for data collection and computer or printer communications



Features

- Vivid, backlit LCD easily visible in any lighting conditions
- Programmable backlight can be set to "always on," "always off" or "light only when weighing"
- Capacity tracker built into display for easily monitoring possible overloads
- Scratch-resistant aluminum housing protects internal components
- · Colour-coded keys facilitate quick recognition of the most frequently used buttons
- Pan lifter allows easy placement and removal of samples
- Optional RS-232 interface is available to provide speedy connection to computers and printers
- USB host for memory card and USB I/O interface
- USB interface included for faster data communication
- Temperature range 50°C to 160°C in one-degree increments
- Three settings for heating sample include ramp-up, stepped temperatures and single temperature
- Seven preset drying modes allow test routines for several products
- Audible overload alarm warns when capacity has been exceeded
- Testing can be set to start automatically when lid closes
- Calibration for temperature and weight
- Multilingual display allows use in many different countries
- Quick and easy configuration using the keypad
- · Zero-tracking feature ensures display returns to zero reading
- Internal memory stores 49 different receipes and up to 99 test results,
- and additional test results and settings can be stored on a flash drive
- Mains power cord

Applications

- Weighing
- Moisture determination

About ADAM:

For more than 40 years, professionals worldwide have relied on Adam Equipment for an extensive selection of dependable and affordable weighing equipment. Adam provides the right balance of speed, performance and value.

PMB Moisture Analyser



Model	PMB 53	PMB 163	PMB 202
Capacity	50g	160g	200g
Readability	0.001g / 0.01%	0.001g / 0.01%	0.01g / 0.05%
Pan Size	100mm ø		
Weighing Units	g, %M, %S, ATRO %M, ATRO %S		
Stabilisation Time (sec)	4		
Memory Settings	Internal memory stores up to 99 test results and 49 programmable user settings External USB drive for limitless data storage of test results and settings		
Interface	RS-232, USB		
Calibration	External calibration		
Display	Backlit LCD with 24mm-high digits		
Power Supply	Mains power cord		
Operating Temperature	0° to 40°C		
Housing	Die-cast aluminum		
Overall Dim.	250x360x185mm (wxdxh)		
NetWeight	бкд		

Accessories

Item number	Description
104008036	
1070010636	. Temperature calibration kit
301208188	. In-use cover
1120011156	. ATP thermal printer
3126011263	. ATP thermal printer paper
3126011281	. ATP thermal printer paper (pack of 10)
3074010266	. RS-232 cable (null-modem)
307140001	. Disposable sample pans (pack of 250)
700100046	. Kensington-type lock and cable
600002028	. Adam DU data collection program
3074010267	. USB cable
700660290	. Calibration certificate
700100014	.F1 50g Calibration Weight
700100007	.F1 100g Calibration Weight
700100012	.F1 200g Calibration Weight

Key Accessories



ATP Thermal Printer

Easy-to-use features combined with quick set-up equals a truly versatile thermal printer. A single push-button feed key and three easyto-read LED indicators make operation simple.



 $\label{eq:constraint} \begin{array}{l} \textbf{Temperature Calibration Kit}\\ The temperature calibration kit comes in a cushioned carrying case for protection and easy transportation. The temperature measuring range is from -50 °C to 300 °C, with readings in Celsius or Farenheit. \end{array}$



Disposable Sample Pans When weighing chemicals or other messy items, the use of disposable pans can help keep the permanent pan clean.

Supplied by

www.adamequipment.com